


Berry Plumbing & Equipment

Model B-GC4016



Model **B-GC4016 Giblet Chiller** from Berry Plumbing & Equipment, designed for use of giblets or paws to quickly reduce temperature after harvesting.



WATER:	PER USDA REQUIREMENTS
ELECTRICITY:	PADDLE—1 HORSEPOWER MOTOR, 208/230-460 V, 3 PHASE, 60 HZ, 1.58 FL AMP ELEVATOR—1 HORSEPOWER MOTOR, 200/300 V, 3 PHASE, 60 HZ. 1.51 AMP
CAPACITY:	APPROXIMATELY 300 GIBLET SETS PER MINUTE
HEIGHT:	Approx. 59" w/ Adjustable Legs
WIDTH:	Approx. 56"
LENGTH:	Approx. 266"



Construction:

The Berry Plumbing & Equipment **Giblet Chiller Model B-GC4016** is constructed entirely of stainless steel and UHMW for durability and easy cleanup.

Operation:

Hearts, livers, gizzards, necks or paws are deposited into the **Model B-GC4016 Giblet Chiller** and agitated by the sweeping paddle which is driven by a one horsepower electric motor. Chilled water and ice in the chiller tank chill the giblets which are then unloaded by the elevator, also chain driven.

Maintenance:

Berry Plumbing & Equipment Company designers and technicians have taken great care in assuring that the **Giblet Chiller** is manufactured with smooth rounded surfaces and easily removable covers to make thorough clean up easy for cleaning personnel. The Elevator Assembly can be removed for cleaning or maintenance.

Options:

Berry's Giblet Chiller is available in a 10' long (B-GC3010) and a 15' long (B-GC3015) model also.

The specifications as stated herein are the most current at the time of publication. However, consistent with our standard of continual product development, we reserve the right to change the design without notice or obligation to modify any equipment previously sold or delivered. 12/31/2000

Berry Plumbing & Equipment 6736 Cleveland Highway, Clermont Georgia 30527 Email: tberry@berryequipment.net Phone: 770-983-3929 Toll Free Fax: 1-866-808-9957 36